

# SC Series 167



Modern plafond supplied with LED light sources.

<b>TECHNICAL DATA</b>	<b>Mounting:</b> directly on the ceiling <b>Body:</b> polycarbonate <b>Colour:</b> white <b>Diffuser:</b> polycarbonate
<b>ELECTRICAL DATA</b>	<b>Power supply efficiency:</b> 90% <b>Power:</b> 220-240V 50/60Hz <b>Includes light source:</b> yes <b>Type of equipment:</b> ED, 110v Dim/Sensor, EM 3h <b>Electrical connection:</b> max 2x1,5 mm <sup>2</sup> wire
<b>OPTICAL DATA</b>	<b>Light distribution:</b> rotationally-symmetric <b>Way of lighting:</b> direct
<b>GENERAL DATA</b>	<b>Lifetime (L70B10):</b> 60 000 h <b>Operating temperature range:</b> -20° C... +45° C <b>Warranty:</b> 5 years <b>Application:</b> public utility facilities, halls, staircases, corridors, hotels



Code	Type of equipment	Luminaire power [W]	Lumen luminaire [lm]	Efficacy [lm/W]	Colour temperature [K]	CRI/Ra
SC167.1075.30K	ED	12	1075	90	3000	≥80
SC167.1075.40K	ED	12	1075	90	4000	≥80
SC167.1450.30K	ED	17	1450	85	3000	≥80
SC167.1450.40K	ED	17	1450	85	4000	≥80

## TECHNICAL INFORMATION

-Stylish contemporary IK10 IP65 LED Bulkhead High performance UL94 polycarbonate body Twist and lock bezel to conceal -fixings Tridonic LED Board and Driver

-IP65 sealed against liquid and dust ingress IK10 Rated - Impact tested to BSEN2262 Dimming and EM options

-Integral sensor options

-Back lit halo effect base option

-Bezel colour finish options

## ADDITIONAL ORDERING CODES

<b>/BL</b> Black Bezel	<b>/ECO</b> SwitchDIM, DALI or DSI
<b>/HALO</b> Back lit halo effect	<b>/SO</b> Integral Sensor On - Off
<b>/AT</b> Anti Tamper gear tray screws	<b>/SD</b> Integral Sensor On - 10% Dim
<b>/ATB</b> Anti Tamper steel bezel - black	<b>/EMI</b> Integral Emergency

Luminous flux tolerance +/- 10%.  
Power tolerance +/- 5%.  
Up-to-date product info and General Warranty Terms available on our website