

# LN SERIES 1

IP20 Indoor Linear

## Product Description

The LN Series 1 delivers up to 7,200 lumens of exceptional light while achieving 120 lumens per Watt. This breakthrough performance is achieved by combining the high efficacy and high-quality light with a unique thermal management approach. The LN Series 1 is available in 3 lengths. The compact, lightweight design easily accommodates surface mount installations, making the LN Series 1 perfect for use in commercial, new construction or retrofit applications.

## Performance summary

**Delivered Light Output:** 2,760 - 7,200 lumens

**Efficacy:** Up to 120 lm/W

**Input Power:** 20 - 60W

**IP Rating:** IP20

**CRI:** >80

**CCT:** 3000K, 4000K, 5500K

**Input Voltage:** 220-240V

**Lifetime:** 50,000 hours L70B50 at 25°C

**Limited Warranty:** 5 years

**Dimensions:** L 1220/1524/1828mm x W 70mm x H 76.5mm

**Mounting:** Surface

**Net Weight:** 1.7 - 2.6kg



## Ordering Information

Example: LN1-48L-40K-DALI-AE

Product	Lumen Output	CCT	Control (optional)	Emergency (optional)
<b>LN1</b> LN Series 1	<b>27L</b> 23W, 2,760 lumens (1220mm)	<b>40K</b> Neutral white 4000K	<b>DALI</b> Touch + DALI	<b>E3</b> Maintained emergency
	<b>44L</b> 37W, 4,400 lumens (1524mm)			<b>ST</b> Self-test emergency
	<b>48L</b> 40W, 4,800 lumens (1220mm)			<b>AE</b> DALI Addressable emergency
	<b>64L</b> 54W, 6,480 lumens (1828mm)			
	<b>72L</b> 60W, 7,200 lumens (1524mm)			